


RG 100-800

Suction fans



info@obera.fr
+33 3 67 10 66 75
www.obera.fr

Suction fans

RG 100-800

Areas of use

- Suction from one or more workstations or machines
- Aspiration of dusts, fumes or solvents
- Possible combination with a dust collector or collection evacuation
- For the suction of a pick-up element

Ideal for :

- Dust
- Gas
- Odors
- Smoke

Benefits

- Strong power
- Robust construction
- Low consumption
- Wide operating range
- Low ground hold thanks to compact design

Options

- RG-100 and RG-200 in alternating current
- Food grade stainless steel
- Engine on the left
- Output diameter variable
- Anti-spark version for flammable dusts

Technical data

EUROSOG		100	200	300	400
Maximum flow rate	m ³ /h	1.000	2.000	3.000	3.200
Diameter inlet / outlet	mm	100	150	180	250/315
Maximum suction	Pa	1.400	1.600	2.300	3.150
Supply voltage	V	400	400	400	400
Power	kW	0.5	1.1	2.2	3.0
Measurements (LxWxH)	mm	535x450x480	595x520x555	640x535x610	711x700x1.012
Sound level	dB(A)	80	82	84	84
Item No.		01.011	01.021	01.031	01.441

EUROSOG		500	600	700	800
Maximum flow rate	m ³ /h	4.000	5.500	7.000	8.000
Diameter inlet / outlet	mm	250/315	315/355	315/400	355/400
Maximum suction	Pa	3.400	3.400	3.400	3.950
Supply voltage	V	400	400	400	400
Power	kW	4.0	5.5	5.5	7.5
Dimensions (L/I/H)	mm	711x700x1.012	737x700x1.062	762x700x1.062	820x1.000x1.198
Sound level	dB(A)	84	84	83	84
Item No.		01.451	01.461	01.471	01.481